


FLOATING AIR™ PRO X | MULTI-ZONE ALLOWABLE CONFIGURATIONS

Choose the outdoor unit that is applicable to the number of indoor spaces you want to heat and cool. Mix-and-match flexibility lets you pick the type of indoor units best suited to the application: wall-mounted, ceiling cassette, concealed ducted, or air handlers.



2 ZONES ONLY
18,000 BTU
24,000 Btu max. connected capacity



2 OR 3 ZONES
27,000 BTU
36,000 Btu max. connected capacity



2, 3, OR 4 ZONES
36,000 BTU
48,000 Btu max. connected capacity

FPHMR18A3D		
ZONE 1	ZONE 2	TOTAL
7	7	14
7	9	16
7	12	19
9	9	18
9	12	21
12	12	24

FPHMR27A3D				
ZONE 1	ZONE 2	ZONE 3	TOTAL	
7	7	-	14	
7	9	-	16	
7	12	-	19	
7	18	-	25	
9	9	-	18	
9	12	-	21	
9	18	-	27	
9	24	-	33	
12	12	-	24	
12	18	-	30	
18	18	-	36	
7	7	7	21	
7	7	9	23	
7	7	12	26	
7	7	18	32	
7	9	9	25	
7	9	12	28	
7	9	18	34	
7	12	12	31	
7	12	18	37	
9	9	9	27	
9	9	12	30	
9	9	18	36	
9	12	12	33	
12	12	12	36	

FPHMR36A3D					
ZONE 1	ZONE 2	ZONE 3	ZONE 4	TOTAL	
7	24	-	-	31*	
9	24	-	-	33*	
12	18	-	-	30*	
12	24	-	-	36*	
18	18	-	-	36*	
18	24	-	-	42*	
24	24	-	-	48*	
7	7	7	-	21	
7	7	9	-	23	
7	7	12	-	26	
7	7	18	-	32*	
7	7	24	-	38*	
7	9	9	-	25	
7	9	12	-	28	
7	9	18	-	34*	
7	9	24	-	40*	
7	12	12	-	31	
7	12	18	-	37*	
7	12	24	-	43*	
7	18	24	-	49	
9	9	9	-	27	
9	9	12	-	30	
9	9	18	-	36*	
9	9	24	-	42*	
9	12	12	-	33	
9	12	18	-	39*	
9	12	24	-	45*	
9	18	24	-	51	
12	12	12	-	36	
12	12	18	-	42*	
12	12	24	-	48*	
18	18	7	-	43*	
18	18	9	-	45*	
18	18	12	-	48*	
7	7	7	7	28	
7	7	7	9	30	
7	7	7	12	33	
7	7	7	18	39	
7	7	7	24	45	
7	7	9	9	32	
7	7	12	12	35	
7	7	9	18	41	
7	7	9	24	47	
7	7	12	12	38	
7	7	12	18	44	
7	7	12	24	50	
7	9	9	9	34	
7	9	9	12	37	
7	9	9	18	43	
7	9	9	24	49	
7	9	12	12	40	
7	9	12	18	46	
7	9	12	24	52	
7	12	12	12	43	
7	12	12	18	49	
9	9	9	9	36	
9	9	9	12	39	
9	9	9	18	45	
9	9	9	24	51	
9	9	12	12	42	
9	9	12	18	48	
9	12	12	12	45	
9	12	12	18	51	
12	12	12	12	48	

■ Floating Air™ Multi-zone allowable combinations that exceed our 100% ratio.

INDOOR UNITS

<p>Wall-mounted</p>	MODEL	BTU
	FAHFW07A3D	7,000
	FAHFW09A3D	9,000
	FAHFW12A3D	12,000
	FAHFW18A3D	18,000
	FAHFW24A3D	24,000
<p>Ceiling cassette</p>	MODEL	BTU
	FPHFC09A3D	9,000
	FPHFC12A3D	12,000
	FPHFC18A3D	18,000
	FPHFC24A3D	24,000
<p>Concealed ducted</p>	MODEL	BTU
	FPHFD09A3D	9,000
	FPHFD12A3D	12,000
	FPHFD18A3D	18,000
	FPHFD24A3D	24,000
<p>Air handler</p>	MODEL	BTU
	FPHFA18A3D	18,000
	FPHFA24A3D	24,000

*Acceptable combination allowed with air handler unit.

FLOATING AIR™ PRO X | MULTI-ZONE ALLOWABLE CONFIGURATIONS



2, 3, 4, OR 5 ZONES

42,000 BTU
54,000 Btu max.
connected capacity

FPHMR42A3D					
ZONE 1	ZONE 2	ZONE 3	ZONE 4	ZONE 5	TOTAL
12	24	-	-	-	36*
18	18	-	-	-	36*
18	24	-	-	-	42*
24	24	-	-	-	48*
7	7	7	-	-	21
7	7	9	-	-	23
7	7	12	-	-	26
7	7	18	-	-	32*
7	7	24	-	-	38*
7	9	9	-	-	25
7	9	12	-	-	28
7	9	18	-	-	34*
7	9	24	-	-	40*
7	12	12	-	-	31
7	12	18	-	-	37*
7	12	24	-	-	43*
7	18	18	-	-	43*
7	18	24	-	-	49*
9	9	9	-	-	27
9	9	12	-	-	30
9	9	18	-	-	36*
9	9	24	-	-	42*
9	12	12	-	-	33
9	12	18	-	-	39*
9	12	24	-	-	45*
9	18	18	-	-	45*
9	18	24	-	-	51*
12	12	12	-	-	36
12	12	18	-	-	42*
12	12	24	-	-	48*
12	18	18	-	-	48*
12	18	24	-	-	54*
7	7	7	7	-	28
7	7	7	9	-	30
7	7	7	12	-	33
7	7	7	18	-	39*
7	7	7	24	-	45*
7	7	9	9	-	32
7	7	9	12	-	35
7	7	9	18	-	41*
7	7	9	24	-	47*
7	7	12	12	-	38
7	7	12	18	-	44*
7	7	12	24	-	50*
7	7	18	24	-	56
7	9	9	9	-	34
7	9	9	12	-	37
7	9	9	18	-	43*
7	9	9	24	-	49*
7	9	12	12	-	40
7	9	12	18	-	46*
7	9	12	24	-	52*
7	9	18	24	-	58
7	12	12	12	-	43
7	12	12	18	-	49*
7	12	12	24	-	55
9	9	9	9	-	36
9	9	9	12	-	39
9	9	9	18	-	45*
9	9	9	24	-	51*
9	9	12	12	-	42
9	9	12	18	-	48*
9	9	12	24	-	54*
9	9	18	24	-	60
9	12	12	12	-	45
9	12	12	18	-	51*
9	12	12	24	-	57
12	12	12	12	-	48
12	12	12	18	-	54*

FPHMR42A3D					
ZONE 1	ZONE 2	ZONE 3	ZONE 4	ZONE 5	TOTAL
7	7	7	7	7	35
7	7	7	7	9	37
7	7	7	7	12	40
7	7	7	7	18	46
7	7	7	7	24	52
7	7	7	9	9	39
7	7	7	9	12	42
7	7	7	9	18	48
7	7	7	9	24	54
7	7	7	12	12	45
7	7	7	12	18	51
7	7	9	9	9	41
7	7	9	9	12	44
7	7	9	9	18	50
7	7	9	12	12	47
7	7	12	12	12	50
7	9	9	9	9	43
7	9	9	9	12	46
7	9	9	9	18	52
7	9	9	12	12	49
7	9	12	12	12	52
9	9	9	9	9	45
9	9	9	9	12	48
9	9	9	9	18	54
9	9	9	12	12	51
9	9	12	12	12	54

*Acceptable combination allowed with air handler unit.